


# T2

THE PERFORMANCE  
SWEET SPOT



ALL-NEW  
CHASSIS

DUAL DAC  
ES9028PRO

DSD512  
22.6MHZ

PCM  
384KHZ

USB  
OUTPUT

INTERNAL  
POWER SUPPLY

# LUMIN

# T2

# LUMIN

ALL-NEW CHASSIS DESIGN  
FEATURING THICK CNC  
PANELS AND AN INTERNAL  
POWER SUPPLY

NEW GENERATION  
PROCESSOR

DUAL ES9028PRO SABRE DAC  
FEATURING DUAL-MONO  
OPERATION


DSD512 22.6MHz  
PCM 44.1~384kHz 16~32-bit

USB DIGITAL AUDIO OUTPUT

PCM & DSD UPSAMPLING

PRECISION 32-BIT INTERNAL  
DIGITAL VOLUME

COMPLETELY REDESIGNED  
ANALOGUE BUFFER WITH X1  
TECHNOLOGY



#### STREAMING PROTOCOL:

UPnP AV protocol with audio streaming extension (OpenHome). Roon Ready. Spotify Connect. TIDAL Connect. Apple AirPlay. Gapless Playback. On-Device Playlist. Multi-Room (Songcast)

#### SUPPORTED AUDIO FILE FORMATS:

**DSD :**  
DSF (DSD), DFF (DSD), DoP (DSD)  
**PCM:**  
FLAC, Apple Lossless (ALAC), WAV, AIFF  
**OTHER:**  
MQA, MP3

#### SUPPORTED SAMPLE RATES & BIT DEPTHS:

PCM, 44.1kHz~384kHz, 16~32-bit, Stereo  
DSD512, 22.6MHz, 1-bit, Stereo

#### UPSAMPLING RATES & BIT DEPTHS:

PCM 384kHz and DSD128 upsampling option for all files up to 192kHz

#### SUPPORTED CONTROL DEVICES:

Apple iOS devices. iOS 8.0 or later required  
Android devices. Android 4.0 (Ice Cream Sandwich) or later required

#### APP FEATURES:

Native support for TIDAL, MQA, Qobuz and TuneIn Radio. Tidal MQA and Qobuz high-res icons to identify high-res music. Multi-room simultaneous playback. Volume control. High-resolution artwork. Artwork caching. Search. Multiple tag handling. Composer tag support. Album-grouping in playlist. Automatic internet links to artists/album/songs. Saving, syncing and restoring of playlists (including Tidal and Qobuz)

#### INPUT:

Gigabit Ethernet Network (1000BASE-T) RJ45  
USB storage, flash drive, USB hard disk (Single-partition FAT32, exFAT and NTFS only)

#### ANALOGUE AUDIO OUTPUT:

XLR balanced, 6Vrms, pin 2 Hot  
RCA unbalanced, 3Vrms

#### DIGITAL AUDIO OUTPUT:

**USB:**  
DSD64-512 2.8-22.6MHz, 1-bit Stereo  
PCM 44.1~384kHz, 16-32-bit Stereo  
**COAXIAL BNC:**  
PCM 44.1kHz~192kHz, 16~24-bit  
DSD (DoP, DSD over PCM) 2.8MHz, 1-bit

#### FINISH:

Raw brushed aluminium  
Black anodised brushed aluminium

#### POWER SUPPLY:

Internal shielded 100~240V AC auto-ranging

#### OTHER:

Leedh Processing lossless digital volume control  
Programme of Continuous Development -  
Firmware-upgradable for further features and enhancements

LUMIN: 350mm (W), 350mm (D),  
60mm (H), 6kg

[WWW.LUMINMUSIC.COM](http://WWW.LUMINMUSIC.COM)