

MUSIC LIBRARY & NETWORK SWITCH



ZERO CONFIG REQUIRED | TRANSFER OVER USB OR NETWORK | DUAL DRIVE CAPACITY | 4-PORT AUDIOPHILE-GRADE SWITCH | 2X SFP FIBRE 2X RJ45 COPPER | ALUMINIUM CHASSIS

LUMÏN



AN ADVANCED DUAL-DRIVE MUSIC SERVER AND 4-PORT AUDIOPHILE-GRADE NETWORK SWITCH

AVAILABLE WITHOUT DRIVES OR WITH 4TB OR 8TB CAPACITY

ZERO CONFIGURATION REQUIRED

AUTOMATICALLY SERVES ALL ADDED MUSIC

2X SFP FIBRE PORTS PROVIDE COMPLETE ISOLATION FROM NETWORK NOISE AND ENABLE EASY OPTICAL NETWORKING

BESPOKE SERVER SOFTWARE UPNP (OPENHOME) COMPATIBLE

USB 3.0 MICRO TYPE B FOR CONNECTION TO COMPUTER FOR FAST TRANSFER

SMB SUPPORT FOR TRANSFERRING OVER THE NETWORK

GIGABIT ETHERNET

THICK SHIELDED CNC CHASSIS CONSTRUCTION

INTERNAL STORAGE: No drives, 4TB (2x 2TB) or 8TB (2x 4TB) 2.5" SSD

SUPPORTED AUDIO FILE FORMATS:

DSD Lossless: DSF (DSD), DIFF (DSD), DoP (DSD) PCM Lossless:

FLAC, Apple Lossless (ALAC), WAV, AIFF Compressed (lossy) Audio: MP3

Note: The 8TB HDD version uses NTFS format for the internal HDD. On a Mac computer, additional software may be needed to access NTFS formatted HDD.

LUMÌN



CONNECTIONS:

LUMIN

USB 3.0 Micro Type B Slave for connection to computer 2x Gigabit Ethernet Network (1000BASE-T) RJ45 2x Industry-standard SFP 2x USB 3.0 Type A reserved for future use

See website for latest software and app specification

WWW.LUMINMUSIC.COM

POWER SUPPLY:

Internal 100–240V AC auto-ranging Low-noise Shielded power supply compartment for reduced interference with delicate electronics

PHYSICAL:

Finish: Black anodised aluminium Raw anodised aluminium

PHYSICAL: 350mm (W), 350mm (D), 60mm (H), 6kg